

INFINITY

— LUXURY WOVEN VINYL —

2016 - 2017



Since 2008, Infinity Fabrics, LLC has offered designers and specifiers the premier floor fashion proven to withstand even the most demanding environments. Our Luxury Woven Vinyl™ (LWV) features a unique, heavy-traffic rated vinyl backing that makes it ideal for indoor and outdoor use on all types of surfaces.

Founded on principles of environmental sustainability, innovative design, and client education, Infinity continues to challenge the status quo. Our products are UV-stable, resistant to fading, and include antimicrobial technology which prevents bacterial growth. Soil and stains are easily removed from LWV, reducing long-term maintenance expense.

LWV quickly solidified its niche in the marine industry where no other product could match in design, performance, or warranty. Infinity then expanded into the recreational vehicle and aerospace industries where woven vinyl had not been introduced. In 2015, Infinity's product line grew to over seventeen collections and 160 colors, including the very popular Seagrass™ collection.

Servicing dealers and aftermarket installers directly, Infinity has removed the industry expectation of a distribution network. This allows for excellent delivery and thorough education in industries where carpet is being replaced by newer technologies.

LWV is available in 8'6" and 10' widths and is offered on two cushion backing thicknesses. It is an excellent choice for heavy contract, hospitality, healthcare, restaurants, fitness centers, country clubs, and retail stores, as well as aviation, recreation vehicles, and marine.

The future is bright for Infinity. 2016 will see the launch of eleven new styles of LWV and two new product lines: Supreme™ Bimini, Awning, and Canvas & Superior™ Upholstery Vinyl.

For product specifications and other technical information, please visit Infinity's website: infinitylww.com





06 Luxury Woven Vinyl™

Tests	08
Backing	09
Warranty	10
Care + Cleaning	13
Installation	14
Green Uses	21

22 Superior™ Upholstery Vinyl

Tests	25
Warranty	26
Care + Cleaning	29

30 Supreme™ Bimini, Awning + Canvas

Tests	33
Warranty	34
Care + Cleaning	37
Contact Us	39



INFINITY

— LUXURY WOVEN VINYL —

Every now and then a product comes along
that revolutionizes an industry.

Changes everything. Makes life better. That
every now and then is now.

Meet Infinity Luxury Woven Vinyl™. Making the
good life better is what we do. And we've done
it with innovative flooring that is breathtaking
and performs beautifully. It's better because
it resists wear, fading, soil, and mold in
settings where performance is essential. It's
revolutionary. It's spectacular.

It's here.

OVERVIEW

INFINITY
— LUXURY WOVEN VINYL —

FIBER CONTENT

Vinyl

BACKING

Frothed Vinyl Memory

WIDTH

8'6" & 10'

THICKNESS

Compact Cushion (CC) .115-.146"

Heavy Duty (HD) .150-.223"

APPLICATION

Heavy Commercial

Marine

Recreation Vehicle (RV)

ADDITIVES

Antimicrobial

WARRANTY

Ten (10) Year Limited

FEATURES AND BENEFITS

Rated for Heavy Commercial Traffic

Soil & Stain Resistant

Mold & Mildew Resistant

Ultra-Violet Stable & Fade Resistant

Easy to Clean

Pet Friendly

Impervious to Gasoline, Grease & Motor Oil

Unaffected by Sea Gull & Spider Defecation

Sound Dampening for Quieter Rides

Made in the USA





TESTS CONDUCTED

Wear/Performance

ASTM 5252 Hexapod Walker 12,000 cyc	Heavy Commercial Traffic Rating
ASTM D3936 Delamination	No Delamination; Superior Traffic Resistance
ASTM D3884 Abrasion Resistance	Superior Abrasion Resistance
Soiling / Cleaning	Superior Soil Resistance
ASTM F925 Chemical Resistance	No Effect; Superior Chemical Resistance
ASTM F150 Electrical Resistance	Electrostatic Resistance
AATCC-134 Static Propensity	Exceeds Static Propensity Expectation
ASTM C1028 Slip Resistance	Exceeds Slip Resistance Expectation
ASTM E303 Skid Resistance	Superior Skid Resistance
ASTM G21 Fungus Resistance	No Growth; Superior Fungal Resistance

Flammability

ASTM E648 Critical Radiant Flux	Class 1
ASTM E662 Optical Smoke Density	Passes
FMVSS 302 Motor Vehicle Safety Standard	Passes
ASTM C-518 R-Factor	Allows Radiant Heat

Individual test results are held at our manufacturing facility and can be provided if required.
 All tests were completed by a certified independent laboratory.

ONE-OF-A-KIND BACKING

Infinity's Luxury Woven Vinyl™ face is directly attached to a frothed vinyl backing. We are the only company in the world with this unique product, setting us apart from all of our competition. We have eleven patents pending.

Vinyl on Vinyl

What does it really mean?

- Both the face and backing of Infinity Luxury Woven Vinyl™ are recyclable.
- It is anti-microbial and anti-bacterial so it does not promote the growth of mildew or mold.
- LWV dries rapidly. Neither the face nor backing can get saturated quickly by any liquid. In fact, if our flooring is submerged in water, it will actually float.
- Conversely, if Infinity flooring is exposed to fire, it will attempt to self-extinguish immediately and will self-extinguish once the direct flame is removed.

Urethane backing

Why should you avoid?

- Competitors use an inferior product with Urethane backing. It cannot be recycled.
- Urethane backing soaks up liquid like a sponge, promoting mold and mildew growth.
- Once submerged, it will remain wet for long periods of time.
- Urethane backing discolors and cracks causing long term issues or requiring immediate replacement.
- Urethane backing burns rapidly and cannot self-extinguish.

WARRANTY COVERAGE - TEN YEAR LIMITED

Infinity Fabrics, LLC warrants to the original purchaser (Buyer) only that woven vinyl flooring product manufactured by Infinity Fabrics, LLC will be free from defects in material and workmanship under normal use and service for a period of ten (10) years from the date of purchase. This warranty shall not apply and no warranty of any kind shall exist if this product has been subject to abuse, misuse, neglect or alteration of any type or cause. In addition, Infinity Fabrics, LLC is not responsible for defects resulting from improper installation or use, disruptions to the subfloor surface causing joint separation or from uses beyond design capability. In addition to the foregoing limitations, Infinity Fabrics, LLC's limited warranty shall not cover surface stains including stains resulting from asphalt, driveway sealer and rubber wheels, defects resulting from improper maintenance or installation, damage from improper usage including, without limitation, burns, cuts, tears, scratches, scuffs, indentation damage from rolling loads, improperly castered carts, damage or discoloration from adhesive or floor care products, extended direct exposure to sunlight, excessive moisture, alkaline, hydrostatic pressure damage from the subfloor, mold or mildew, installation over gypsum based patching and leveling compounds or difference in color between samples or photographs and the actual flooring. Infinity Fabrics, LLC, in its sole discretion, shall determine whether or not the product is defective or otherwise covered or not covered by this warranty. No action for breach of this warranty may be commenced more than one (1) year after occurrence of the alleged breach. This warranty is not transferable. Customer must notify Infinity Fabrics, LLC of all manufacturer defects within 60 days of purchase. Proof of purchase date will be required.



WARRANTY



Limitation of Liability

Infinity Fabrics, LLC shall not be liable for the loss of use, loss of time, inconvenience, loss of revenue or any other indirect, consequential, special or incidental damages whether based upon breach of the above warranty, breach of contract, negligence, tort or under any other legal theory. Infinity Fabrics, LLC makes no warranties of any kind, expressed or implied, other than as herein expressly provided and Infinity Fabrics, LLC specifically disclaims the implied warranties of merchantability and fitness for a particular purpose. Some states do not allow limits on warranties, or on remedies for breach in certain transactions, so the above limitation may not apply.

Exclusive Remedy

Buyer's remedy for breach of Infinity Fabrics, LLC warranty is repair or replacement, at Infinity Fabrics, LLC's option, within a reasonable time after notice of defect. In the event that Infinity Fabrics, LLC is unable to repair such product, Infinity Fabrics, LLC at its option, shall either replace the defective product or refund the purchase price thereof. These remedies are the exclusive remedies for breach of Infinity Fabrics, LLC warranty. Infinity Fabrics, LLC shall not be liable for any other charges incurred, including installation cost, as a result of a defective product. In the event that Buyer makes any claim under Infinity Fabrics, LLC warranty, Infinity Fabrics, LLC reserves the right to require any product to be returned for inspection at Buyer's expense, to Infinity Fabrics, LLC factory in Dalton, GA. No employee of Infinity Fabrics, LLC or any other person is authorized to make any additional warranty or to change this Warranty. Only Infinity Fabrics, LLC is authorized to provide warranty service. For warranty information, please call, email or write to:

Customer Service
5211 Mitchell Bridge Rd NE
Dalton, GA 30721,

Phone: (706) 529-2241

Email: customerservice@infinitylww.com



CARE + CLEANING

INFINITY
— LUXURY WOVEN VINYL —

One of the best ways to keep Luxury Woven Vinyl™ fabric looking good is to hose fabrics off on a weekly basis with clean water. This helps prevent dirt from becoming deeply embedded in the fabric and eliminates the need for more vigorous cleaning. In most environments, a thorough cleaning will be required as soiling dictates. When it's time for a thorough cleaning, Luxury Woven Vinyl™ fabrics can be cleaned while installed.

General or Light Cleaning

To clean Luxury Woven Vinyl™:

- Brush off loose dirt.
- Hose down.
- Prepare a solution of water and mild soap such as dishwashing liquid or household cleaner.
- Apply a small amount of water and soap mixture to LWV.
- Use a soft bristle brush to clean.
- Rinse thoroughly until all soap residue is removed.
- Air dry.
- May not require re-treatment depending on the soiling level of the fabric.

If stubborn stains persist, use a diluted bleach/soap mixture for spot cleaning of mildew. For roof run-off or other similar stains, a strong degreaser may be required.

Heavy Cleaning for Stubborn Stains and Mildew

Luxury Woven Vinyl™ fabrics do not promote mildew growth; however, mildew may grow on dirt and other foreign substances that are not removed from the fabric. To clean stubborn stains:

- Prepare a solution of 1 cup bleach and 1/4 cup mild soap per gallon of clean water.
- Apply small amount of bleach & soap mixture.
- Blot stain with a sponge or clean towel.
- Rinse thoroughly to remove all soap residue.
- Air dry.

Remember to protect the area around your Luxury Woven Vinyl™ fabric if using a bleach solution. Other fabrics that are not made by Infinity may have an adverse reaction to the bleach.

Professional Cleaners

In evaluating the services of a professional cleaning firm, you should inquire about a firm's experience in working with Luxury Woven Vinyl™ fabrics.

Helpful Hints

Always rinse Luxury Woven Vinyl™ thoroughly to completely remove bleach. Please be aware of the environment. Bleach can have harmful effects on the natural environment around you. We do not advise using bleach if you are surrounded by a body of water. Luxury Woven Vinyl™ should only be allowed to air dry.

This information is a guideline, not a guarantee and does not relieve the user from the responsibility of proper care, cleaning and use of the Product and all cleaning agents. Infinity cannot be responsible when unknown changes are made by the manufacturer of the cleaning agent to their formulations. The use of certain cleaning agents, including but not limited to powdered abrasives, solvents, industrial strength cleaners and power washing is not recommended and can be harmful to the surface appearance and the lifespan of the Product. The Supplier & its agents assume no responsibility resulting from the use of such cleaning agents or procedures to the vinyl and use of such will void the warranty.

PREPARING FOR INSTALLATION

1. Preparing Infinity Luxury Woven Vinyl™ (LWV) for Installation

- 1.1. Goods must be rolled face out, cushion in. Do not crease fabric. All claims and warranties voided if rolled any other way or if product has been cut, fitted, or installed.
- 1.2. Before cutting, check the following: Product Quality, Color, Style, and Dimensions.
 - 1.2.1. Product's weave may not run parallel to the cut edge. Due to the fabric's weaving process, some wave, bow, or skew is normal. Tolerance level is 1.5" in either direction.
 - 1.2.2. It is normal for some patterns to exhibit light or dark shading. This shading can be more evident at seams where two pieces of the same style meet.
 - 1.2.3. If fabric does not meet expectations, please contact Infinity's customer support.
- 1.3. For 10' width fabric, trim off selvage. Trim flat on table with a straight edge, using a new razor blade for each cut. Always cut product from the face side of the fabric. Dull blades may damage the product or produce rough edges. Clean cuts allow for reduced seam visibility. No matter how clean the cut, woven vinyl installations typically show seams.
 - 1.3.1. Note that "T" seams are not recommended with woven vinyl.
- 1.4. Delaminating issues, while not common, can be resolved by spray glue or seam sealer injections. If the area to be repaired is near an outer edge, pull back the face fabric and spray the area with a multipurpose glue. If the area to be repaired is further in, an injectable adhesive is required. Inject the site using seam sealer—depth should be no greater than 1/32" (just through the face fabric). Weight should be applied with both repair methods.

2. Preparing Floor for Installation

- 2.1. Floor must be smooth, clean, flat, and dry—no dirt, dust, wax, glossy paint, or any other foreign material. Uneven surfaces should be sanded smooth or filled until surface is completely flat, clean, and dry. Non-wood floors must be fully cured, structurally sound, and free of curing or parting agents. Glossy or metallic surfaces should be sanded to dull the surface.
- 2.2. If floor is made of multiple wooden planks, ensure that the entire floor is level and that there are no gaps or unfilled space between planks. Joints between planks should be level and smooth. Woven vinyl flooring looks best when installed on a completely flat surface.

3. Preparing Wall for Installation

- 3.1. Wall must be smooth, clean, flat, and dry — no dirt, dust, wax, glossy paint, or any other foreign material. Uneven surfaces should be sanded smooth or filled until surface is completely flat, clean, and dry. Concrete walls must be fully cured, structurally sound, and free of curing or parting agents. Glossy surfaces should be sanded to dull the surface.
- 3.2. A wall covering primer is recommended. Wall covering primer ensures that coverings are well-adhered, helps seams stay as tight as possible, and allows for easy removal.
- 3.3. Lining walls before installing woven vinyl is not required. Installers using paper or canvas liners should use the same adhesive for lining as they will for Infinity Luxury Woven Vinyl™.



INSTALLING ON FLOORS

4. Installing Luxury Woven Vinyl™ (LWV) on Floors

- 4.1. This product has a vinyl back and must be installed using a solvent-free, latex-resin adhesive that works with vinyl. Many adhesives are specifically designed for the installation of most outdoor and marine carpets. Adhesive should also be nonflammable and freeze-thaw stable. For additional security, LWV can also be stapled down to wooden surfaces, applying staples along the edges.
- 4.2. Adhesive and woven vinyl must be acclimated on-site. The minimum temperature should be no less than 65°F for 24 hours before, during, and 24 hours after the installation.



INSTALLATION

INFINITY
— LUXURY WOVEN VINYL —

- 4.3. Product should be spread flat and laid open for up to 30 minutes before applying to the floor. This method ensures best adhesive transfer – a 100% transfer of adhesive onto the foam backing must be obtained.
- 4.4. Adhesive should be applied with a paint roller or trowel to the floor only. If a trowel is used, ensure proper trowel notch will achieve a 100% transfer of adhesive to fabric. Different adhesive types will recommend different trowel specifications. Allow adhesive to develop tack before placing the woven vinyl. Do not allow the adhesive to dry or develop a skin. Pull woven vinyl back periodically to check for proper adhesive transfer.
- 4.5. Use a dry paint roller, plastic smoother, or similar tool to remove air bubbles and to ensure fabric has made good contact with the floor. Use scissors or razor knife to trim edges.
- 4.6. Use a seam roller to flatten edges at seams and edges. Seams will be visible using woven vinyl fabric.
- 4.7. If installation will have seams, do not glue LWV to LWV—vinyl will not adhere to itself. Overlap the second strip of LWV with the first strip, double cut, and smooth out firmly. Care must be taken to avoid damaging the subfloor. Excess trimmed edge should be removed from the floor and seam closed within one hour. Repeat for each seam.
 - 4.7.1. Note that due to the weaving process, some bow and skew may be expected. Keep these natural variations in mind when seaming LWV.
- 4.8. Clean up any wet adhesive with soapy water. A soft bristle brush can also be used. Blot dry with a clean towel, and be sure to wash any other surfaces clean of adhesive. Dried adhesive should be removed with an adhesive remover.

INSTALLING ON WALLS

5. Installing Luxury Woven Vinyl™ (LWV) on Walls

- 5.1. This product has a vinyl back and must be installed using a paste/adhesive that works with vinyl. Use a high quality, heavy duty adhesive for high weight wall coverings.
- 5.2. Paste/Adhesive and woven vinyl must be acclimated on-site. The minimum temperature should be no less than 65°F for 24 hours before, during, and 24 hours after the installation. Product should be spread flat and laid open for up to 30 minutes before applying.
- 5.3. Paste/Adhesive should be applied with a paint roller or trowel to the wall. If a trowel is used, ensure proper trowel notch will achieve a 100% transfer of adhesive to fabric. Different adhesive types will recommend different trowel specifications. Allow glue to develop tack before placing the woven vinyl. Do not allow the adhesive to dry or develop a skin. Pull woven vinyl back periodically to check for proper adhesive transfer.
 - 5.3.1. Test a small piece to determine the amount of adhesive to apply and the length of the time adhesive should be allowed to tack up before hanging fabric.
- 5.4. Hang the first strip to a plumb line, allowing overlap with the ceiling and baseboard. Tacking woven vinyl at the ceiling is recommended due its heavy weight. Use a paint roller, plastic smoother, or similar tool to remove air bubbles and to ensure that the fabric has made good contact with the wall. Use scissors or razor knife to trim product at the ceiling, baseboards, etc.
- 5.5. Use a seam roller to flatten edges at seams, ceiling, and baseboard. Seams will be visible using woven vinyl fabric. If fabric is unbacked, be careful not to press too hard against the surface when removing any bubbles or wrinkles that may appear. Too much pressure can cause adhesive to bleed through the fabric, resulting in stains.
- 5.6. Place the second strip at the edge of the first strip (or overlap and double cut) and smooth it out firmly. If double cutting, care must be taken to avoid scoring the wallboard underneath. A double cutting tool or seam pad is required. Excess trimmed edge should be removed from the wall and seam closed within one hour. Repeat for each seam.
 - 5.6.1. Note that due to the weaving process, some bow and skew may be expected. Keep these natural variations in mind when seaming LWV.

INSTALLATION

INFINITY
— LUXURY WOVEN VINYL —

- 5.7. Do not overlap fabric at the seams; vinyl will not adhere to itself. Seams should not be located closer than 6" to corners. Woven vinyl can be installed in corners by using angle irons to keep product flat and at a 90° angle.
- 5.8. Clean up any wet adhesive with soapy water. A soft bristle brush can also be used. Blot dry with a clean towel, and be sure to wash ceilings and baseboards clean of adhesive. Dried adhesive should be removed with an adhesive remover.





BERKSHIRE



QWEST

GREEN USES

INFINITY
— LUXURY WOVEN VINYL —

Infinity is passionate about the environment. If you have ordered a little more than necessary for the installation, here are some great uses for LWV. For more ideas or to share a way you utilized LWV creatively, please contact us at marketing@infinitylww.com.



Tradewinds Coach knows how to make a great first impression.



Make a splash, and cannonball off this Bennington deck.



Set the table, and don't worry about those wine spills.



Tonka Auto & Marine's decorative accents in a Sea Ray

SUPERIOR

— UPHOLSTERY VINYL —

Superior™ stands out in a crowded market of upholstery vinyl offerings. Upholstery began as a leather product which could not withstand the harsh elements.

Soon thereafter, vinyl and polyurethane became what is now the industry standard.

Superior™ upholstery vinyl, by Infinity, supersedes current product lines by offering a seven year UV/fade warranty.

Superior™ lives up to its name with its unique antimicrobial technology and assurances against yellowing and pinking.

Innovation and quality are the hallmarks of Superior™, the premier upholstery vinyl in the marketplace.

OVERVIEW

SUPERIOR
— UPHOLSTERY VINYL —

FIBER CONTENT

Vinyl

BACKING

100% Woven Polyester

WIDTH

54"

ROLL LENGTH

30 Linear Yards

THICKNESS

22 mil

STYLES & COLORS

Leatherette - 31 colors

Carbon Fiber - 20 colors

APPLICATION

Marine

Recreation Vehicle (RV)

Automotive

ADDITIVES

Antimicrobial

WARRANTY

Seven (7) Year Limited

FEATURES AND BENEFITS

Anti-Microbial: No Bacterial Growth

Mold & Mildew Resistant

Appearance Retention

Ultra-Violet Stable & Fade Resistant

Pinking Resistant

Yellowing Resistant

Seven (7) Year UV/Fade Limited Warranty





PREMIER



COACH

TESTS CONDUCTED

Wear/Performance

ASTM D 751 79 Weight (+/-10%OZ/Lin Yd)	30
ASTM D 751 Thickness (+/-10%mm)	0.90
ASTM D 751 Tensile Strength (LBS)	
WARP	80
WEFT	70
ASTM D 751 Tear Strength (LBS)	No Effect; Superior Chemical Resistance
WARP	6
WEFT	6
Surface Abrasion	50000
ASTM D 191A-5874 Cold Crack (-10°F)	Pass
QUV-B	Pass
Oil/Sulfide Stain Resistance	Superior Soil Resistance
ASTM G21 Fungus Resistance	No Growth; Superior Fungal Resistance
ASTM E1428	Super Stain Resistant
AATCC 164-01 NO2	Superior Colorfastness

Flammability

ASTM E648 Critical Radiant Flux	Class 1
ASTM E662 Optical Smoke Density	Passes
FMVSS 302 / CAL 117 SECTION E	Passes
ASTM C-518 R-Factor	Allows Radiant Heat

Individual test results are held at our manufacturing facility and can be provided if required.
All tests were completed by a certified independent laboratory.

WARRANTY COVERAGE - SEVEN YEAR LIMITED

Subject to the limitations and conditions described herein, Infinity Fabrics LLC (Supplier), warrants to its customers, that all marine/RV quality vinyl coated fabrics purchased from Supplier (Product) will conform to the applicable product specifications published by Supplier and will remain free from defects in material and workmanship for a period of seven (7) years (the Warranty Period) from the date of production of a boat or completed trim component part, provided that such Product is applied, installed, used and maintained in accordance with Supplier's specifications and instructions. All warranty claims must be submitted in writing within thirty (30) days after discovery of nonconformity or defect and accompanied by representative samples of such.

During years one and two of the Warranty Period, the Supplier will provide replacement Product to replace any product deemed defective and will pay competitive labor rates for the replacement not to exceed twenty (\$20.00) US Dollars for each yard of replacement Product. During the remainder of the Warranty Period, the Supplier will provide Product to replace defective Product, but will not pay labor or any other associated costs.

Infinity customers should submit any warranty claims to the following address:

Infinity Fabrics, LLC
5211 Mitchell Bridge Rd. NE
Dalton, GA 30721

Phone: (706) 529-2241

Email: customerservice@infinitylww.com



WARRANTY

SUPERIOR
— UPHOLSTERY VINYL —

Vinyl must be available for inspection and analysis by an authorized representative of Infinity before any settlement can be made.

The warranties set forth here do not cover, and are not applicable to, any of the following; (1) bleeding from adjacent boat components, (2) staining due to tanning lotion, teak oil, topping, engine grease, or similar contaminants, (3) degradation due to the presence of amines in adjacent foam cushioning, (4) damage caused by improper installation for failure to seal or trim parts, (5) deterioration due to the use of improper cleaning materials or procedures, (6) staining or degradation due to an agent or cleaner, (7) damage resulting from abuse or power washing, or (8) normal wear and tear.

Subject to Customer's compliance with a written conformance program documented to Supplier's satisfaction and approved in writing, Supplier may expand its warranty to cover staining resulting from mildew growth on adjacent boat components, referred to as "pink staining". To be eligible for consideration Customer's conformance program must include the following:

- Component parts must be treated to resist fungal growth.
- Conformance to ASTM G21 and ASTM 1428 must be verifiable.
- Upholstery must be properly maintained as specified in Suppliers Care and Cleaning Instructions.
- Foam lamination of Product must be provided by Supplier.

THE REMEDIES SET FORTH ARE THE SOLE AND EXCLUSIVE REMEDIES AVAILABLE TO ANY PERSON FOR DEFECTIVE PRODUCTS. UNDER NO CIRCUMSTANCES SHALL SUPPLIER BE LIABLE FOR ANY LOSS, INJURY, EXPENSE OR DAMAGE, WHETHER DIRECT OR CONSEQUENTIAL, INCIDENTAL OR OTHERWISE, RESULTING FROM THE USE OF ANY PRODUCT OR CAUSED BY ANY DEFECT, FAILURE, OR MALFUNCTION OF ANY PRODUCT, WHETHER BASED UPON WARRANTY, CONTRACT, NEGLIGENCE, OR OTHERWISE. THE WARRANTIES SET FORTH HEREIN ARE IN LIEU AND EXCLUDE ALL OTHER WARRANTIES, GUARANTEES, OR REPRESENTATIONS, WHETHER MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.



CARVER



TIARA YACHTS

Marine/RV grade vinyl, like all upholstery, requires a regularly scheduled cleaning program on a daily, weekly, or monthly basis, depending upon the exposure to dirt and/or other staining agents. It is important that efforts begin immediately after a spill to remove any potential staining agent.

Step 1:

Most common everyday light soiling can be easily removed using a solution of 10% liquid dish detergent and 90% warm water, applied with a clean cloth. Rinse with a clean cloth dampened with water and allow area to dry thoroughly. Moderate scrubbing with a soft bristle brush will help loosen dirt and grime embedded in the grain of the vinyl.

Step 2:

For more stubborn stains and heavy soiling, dampen a soft white cloth with Tilex® (or a similar product) or a mild detergent. Gently rub and then rinse with a clean cloth and water. Please note: do not use any "citrus formula" cleaners.

Step 3:

For the most difficult stains or surface mildew, dampen a clean white cloth with a solution of 10% household bleach and 90% water. Rub gently and rinse with water.

This information is a guideline, not a guarantee and does not relieve the user from the responsibility of proper care, cleaning and use of the Product and all cleaning agents. Infinity cannot be responsible when unknown changes are made by the manufacturer of the cleaning agent to their formulations. The use of certain cleaning agents, including but not limited to powdered abrasives, solvents, industrial strength cleaners and power washing is not recommended and can be harmful to the surface appearance and the lifespan of the Product. The Supplier and its agents assume no responsibility resulting from the use of such cleaning agents or procedures to the vinyl and use of such will void the warranty.

SUPREME

— BIMINI, AWNING & CANVAS —

Supreme™ is highly anticipated as an alternative to acrylic and polyester awning fabrics. The first bimini, awning, and canvas material made of woven vinyl, Supreme™ offers the vibrant look of acrylic, but is more colorfast with less degradation. Even in the brightest sun, Supreme™ offers years of carefree service with the best warranty in the marketplace:

ten year limited UV/fade warranty.

Infinity has once again introduced a product drastically different from anything else available. Supreme™ will become the most trusted awning fabric guaranteed against the elements.

OVERVIEW

FIBER CONTENT

Vinyl

WIDTH

60"

WEIGHT

19.5 oz per sq yard

COLORS

20 Stock Colors Available

APPLICATION

Heavy Commercial

Marine

Recreation Vehicle (RV)

ADDITIVES

Antimicrobial

WARRANTY

Ten (10) Year Limited

FEATURES AND BENEFITS

Soil & Stain Resistant

Mold & Mildew Resistant

Appearance Retention

Ultra-Violet Stable & Fade Resistant

Easy to Clean

Unaffected by Sea Gull & Spider Defecation

Ten (10) Year UV/Fade Limited Warranty

Made in the USA





TESTS CONDUCTED

Wear/Performance

ASTM D4157 Abrasion Resistance	Superior Abrasion Resistance Exceeds 50,000 cycles
AATCC 127 Hydrostatic	16cm; Breathable
ASTM D751 Continual Tear Resistance	12.8 lbs; Industrial Strength
ASTM D2261 Tongue Tear Resistance	12.8 lbs Cross Direction; 19.7 lbs Machine Direction
ASTM D5034 Grab Tensile Strength (LBS)	Industrial Strength
WARP	225.9
WEFT	164
ASTM D5804 Zero Span Tensile Strength	Industrial Strength
WARP	242.5
WEFT	160.1
ASTM D2594 Stretch	1.33% Stretch; .82% Fill; No Loss in Shape
ASTM D4851 Adhesion	No Delamination
AATCC 16 Colorfastness	1,500 AFU No change
Heat Aging	No color change, cracking, crazing or obvious detrimental change
Soiling / Cleaning	Superior Soil Resistance
ASTM G21 Fungus Resistance	No Growth; Superior Fungal Resistance

Flammability

NFPA 701, Test 1 Propagation of Flame	Passes
NFPA 701, Test 2 Propagation of Flame	Passes
ASTM E84 Surface Flammability	Class A for Flame Spread & Smoke; Superior

Individual test results are held at our manufacturing facility and can be provided if required.
All tests were completed by a certified independent laboratory.

WARRANTY COVERAGE - TEN YEAR LIMITED

We stand behind our fabrics with a guarantee that's the best in the industry: a ten (10) year warranty for Supreme™ as decorative shade fabrics and for shade and marine fabrics.

This warranty covers Supreme fabric only. This warranty does not cover normal care and cleaning; damage from misuse or abuse; improper installation; or costs associated with replacement of the fabric, including labor and installation. Infinity's liability is expressly limited to this warranty. Infinity reserves the right to inspect the fabric submitted for claim. Infinity will supply new equivalent fabric to replace the fabric that becomes unserviceable.

This warranty applies to the original purchaser of Supreme fabric and protects against Supreme fabric becoming unserviceable due to color or strength loss from normal usage and exposure conditions, including sunlight, mildew and atmospheric chemicals.



WARRANTY



The warranty coverage period is ten (10) years from the original purchase date. Infinity will provide replacement fabric at no cost during years one through eight, at the then-current selling price less a 15% discount during the ninth year; and less a 30% discount during the tenth year.

Infinity customers should submit any warranty claims to the following address:

Infinity Fabrics, LLC
5211 Mitchell Bridge Rd. NE
Dalton, GA 30721

Phone: (706) 529-2241

Email: customerservice@infinitylww.com

Fabric must be available for inspection and analysis by an authorized representative of Infinity before any settlement can be made.

The warranties set forth here do not cover, and are not applicable, to any of the following; (1) staining due to tanning lotion, teak oil, topping, engine grease, or similar contaminants, (2) damage caused by improper installation, (3) deterioration due to the use of improper cleaning materials or procedures, (4) staining or degradation due to an agent or cleaner, (5) damage resulting from abuse or power washing, or (6) normal wear and tear.

THE REMEDIES SET FORTH ARE THE SOLE AND EXCLUSIVE REMEDIES AVAILABLE TO ANY PERSON FOR DEFECTIVE PRODUCTS. UNDER NO CIRCUMSTANCES SHALL SUPPLIER BE LIABLE FOR ANY LOSS, INJURY, EXPENSE OR DAMAGE, WHETHER DIRECT OR CONSEQUENTIAL, INCIDENTAL OR OTHERWISE, RESULTING FROM THE USE OF ANY PRODUCT OR CAUSED BY ANY DEFECT, FAILURE, OR MALFUNCTION OF ANY PRODUCT, WHETHER BASED UPON WARRANTY, CONTRACT, NEGLIGENCE, OR OTHERWISE. THE WARRANTIES SET FORTH HEREIN ARE IN LIEU AND EXCLUDE ALL OTHER WARRANTIES, GUARANTEES, OR REPRESENTATIONS, WHETHER MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.



One of the best ways to keep Supreme™ woven vinyl fabric looking good is to hose fabrics off on a weekly basis with clean water. This helps prevent dirt from becoming deeply embedded in the fabric and eliminates the need for more vigorous cleaning. In most environments, a thorough cleaning will be required as soiling dictates. When it's time for a thorough cleaning, Supreme™ woven vinyl fabrics can be cleaned while still on a boat or while still installed as an awning, etc.

General or Light Cleaning

To clean Supreme™ while still on a boat:

- Brush off loose dirt.
- Hose down.
- Prepare a solution of water and mild soap such as dishwashing liquid or household cleaner.
- Apply a small amount of water and soap mixture to Supreme™ fabric.
- Use a soft bristle brush to clean.
- Rinse thoroughly until all soap residue is removed.
- Air dry.
- May not require re-treatment depending on the soiling level of the fabric.

If stubborn stains persist, use a diluted bleach/soap mixture for spot cleaning of mildew. For roof run-off or other similar stains, a strong degreaser may be required.

Heavy Cleaning for Stubborn Stains and Mildew

Supreme™ fabrics do not promote mildew growth; however, mildew may grow on dirt and other foreign substances that are not removed from the fabric. To clean stubborn stains:

- Prepare a solution of 1 cup bleach and 1/4 cup mild soap per gallon of clean water.
- Apply small amount of bleach & soap mixture.
- Blot stain with a sponge or clean towel.
- Rinse thoroughly to remove all soap residue.
- Air dry.

Remember to protect the area around your Supreme™ fabric if using a bleach solution. Other fabrics that are not made by Infinity may have an adverse reaction to the bleach.

Professional Cleaners

In evaluating the services of a professional cleaning firm, you should inquire about a firm's experience in working with Supreme™ fabrics.

Helpful Hints

Always rinse Supreme™ thoroughly to completely remove bleach. Please be aware of the environment. Bleach can have harmful effects on the natural environment around you. We do not advise using bleach if you are surrounded by a body of water. Supreme™ should only be allowed to air dry.

This information is a guideline, not a guarantee and does not relieve the user from the responsibility of proper care, cleaning and use of the Product and all cleaning agents. Infinity cannot be responsible when unknown changes are made by the manufacturer of the cleaning agent to their formulations. The use of certain cleaning agents, including but not limited to powdered abrasives, solvents, industrial strength cleaners and power washing is not recommended and can be harmful to the surface appearance and the lifespan of the Product. The Supplier & its agents assume no responsibility resulting from the use of such cleaning agents or procedures to the vinyl and use of such will void the warranty.

CONTACT US



Dear Valued Customers,

Here is a list of our key email addresses. Please use this as a guide to place orders, request samples, or discuss billing matters:

Orders:	orders@infinitylww.com
Samples:	samples@infinitylww.com
Finance:	finance@infinitylww.com
Customer Service:	customerservice@infinitylww.com

To assist in the selection of all products, Infinity's website now includes high resolution, color corrected swatches of Luxury Woven Vinyl™ Floor and Wall Covering, Superior™ Upholstery Vinyl, and Supreme™ Bimini, Awning, and Canvas. You can shop by color, collection, and product line. The enhanced website also contains a new press section, a downloadable product guide, and a fantastic gallery of installation photos. Use this as a sales tool in your showroom or on your handheld device!

Be sure to connect with us on Facebook, Instagram, Google+, Twitter, Pinterest, and LinkedIn. We love sharing your installation photos through our social media channels!

We look forward to continually growing our business right alongside yours!

Best,

A handwritten signature in black ink that reads "Steve Couch".

Steve Couch

President and CEO



facebook



instagram



google +



twitter



pinterest



linked-in



youtube



G3 BOATS



LANDAU



BENNINGTON



LOWE BOATS

INFINITY
— LUXURY WOVEN VINYL —

infinitylww.com

5211 Mitchell Bridge Rd. NE | Dalton, GA 30721 | p. 706.529.2241 | f. 706.529.2243