

# POWER BIMINI TOP INSTRUCTIONS FOR PROPER OPERATION

#### NOTICE

- **ALWAYS** have the protective boot installed, except for the FULL OPEN position.
- ALWAYS remain on the UP/DOWN button until the unit turns itself off.
- ALWAYS store the PWR-ARM in the Full Down position with the boot on when
  not in use.

#### WARNING

- NEVER attempt to operate the top while the boat is in motion.
- NEVER exceed 25 MPH without the boot properly installed.
- NEVER open the top in excessively high winds.
- **NEVER** trailer the boat without the boot on in the full down position



## **FULL OPEN POSITION- MAXIMUM SHADE**

## **Proper Operation**

- 1. Remove protective boot
- Depress and hold UP button on helm until motors turn off on their own – do not release button until motors turn off
- 3. Speed Limit in this position 25 MPH
- 4. Do not open in excessively high winds



## **VARI-PITCH POSITION – SHADE DURING LOW SUN**

#### **Proper Operation**

- 1. Remove protective boot
- 2. Depress and hold UP/DOWN button on helm until desired position is reach and then release button.
- 3. Speed Limit in this position 5 MPH
- 4. Do not open in excessively high winds



# RADAR POSITION – REAR ENTRY/EXIT

### **Proper Operation**

- 1. Install protective boot
- 2. Depress and hold UP button on helm until motors turn off on their own do not release button until motors turn off
- 3. Speed Limit in this position 50 MPH



## FULL DOWN POSITION – LIFTS/BRIDGES/STORAGE

## **Proper Operation**

- 1. Install protective boot for storage and road travel.
- 2. Depress and hold DOWN button on helm until motors turn off on their own
- 3. Speed Limit with boot installed 65 MPH
- 4. Speed Limit without boot installed <u>5 MPH</u>